



\* NOTE: All relevant materials are complied with RoHS directive .

	PCB: UTS-422/485 VER.B_C, W/IC: FT232BL+(ADM3491AR*2)	1	
6	PLASTIC HOOD COLOR TRANSPARENT	1set	
	MOLDED PVC GREY (M45GY036)		M304
5	MOLDED PVC GREY (M45GY036)		M304
4	USB CABLE 2.0, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, OD 4.7mm, JACKET SILVER SATN(422C), DRAWING No. EUAB2801P2402C-145	L-50mm	M304
3	HEX-NUT 4.75*8.5mm	2	
2	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR, PCB TYPE	1	
1	USB A MALE 2.0, GOLD PLATING 30u" ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	1set	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm±
CHECKED	HU		
DRAWING	JUDY		
DATE	02/SEP/10	ITEM NO.	UNIT:mm

