

USB to RS-422 Adapter

USB to RS-422 adapter provides an extra Serial Com port via USB connection and can be configured to work with RS-422 peripherals such as POS and Industrial Control devices. USB Plug and Play feature supports an easy serial port expansion and requires no IRQ, DMA, or I/O port resources.

USB adapter features a full set of RS-422 data and control signals on its terminal block connector. It supports data transfer rates of up to 3 Mbps. No external power supply is required as USB adapter takes its power from the USB bus.

Features:

- Full compliance with the USB Specification 2.0 & 1.1
- Supports the asynchronous serial interfaces
- Data transfers rate 300 to 3M baud
- Supports remote wake-up and power management
- Supports default ROM or external EEPROM for device configuration
- Compatible with Windows 98SE / ME / 2000 / XP / Vista / 7 / 8 / 8.1 / 10 or higher, Win CE, Windows server 2003 / 2008 / 2008R2 / 2012 / 2012R2 or higher; Mac OS 8.6 / 9.x / 10.x, Linux 1.5.0 or higher
- The system is equipped with USB Host Controller

Specification

Model. No	UTS-422	
Chip	FTDI	
Speed	300 to 3M baud	
LED	3	
Compliant	USB spec. 2.0 & 1.1	
Mode	RS-422	
Connector	Upstream	USB Type A Male
	Downstream	DB-9 Male
Power Mode	Bus	
Housing	PVC Molding	

