

# USB to RS-422 Adapter (Terminal Block)

USB to RS-422 adapter provides an extra Serial Com port via USB connection and can be configured to work with RS-422 peripherals such as POS and Industrial Control devices. USB Plug and Play feature supports an easy serial port expansion and requires no IRQ, DMA, or I/O port resources.

USB adapter features a full set of RS-422 data and control signals on its terminal block connector. It supports data transfers rate from 300 to 3M baud. No external power supply is required as USB adapter takes its power from the USB bus.

## Features:

- Full compliance with the USB Specification 2.0 & 1.1
- Supports the asynchronous serial interfaces
- data transfers rate 300 to 3M baud
- Supports remote wake-up and power management
- Supports default ROM or external EEPROM for device configuration
- Compatible with Windows 98SE / ME / 2000 / XP / Vista / 7 / 8 / 8.1 / 10 or higher, Win CE, Windows server 2003 / 2008 / 2008R2 / 2012 / 2012R2 or higher; Mac OS 8.6 / 9.x / 10.x, Linux 1.5.0 or higher
- The system is equipped with USB Host Controller

## Specification

Model No.	UTS-422TB	
Chip	FTDI	
Data Transfers rate	300 to 3M baud	
LED	3	
Compliant	USB spec.1.1	
Mode	RS-422	
Connector	Upstream	USB Type A Male
	Downstream	Terminal Block
Power Mode	Bus	
Housing	Plastic	

